

7 Reasons to Consider the ProCair Prime



**Fowler Boost available
on King Single model*

1. VERSATILITY

The ProCair Prime can be used as a fully alternating pressure mattress (dynamic mode) or easily converted to hybrid mode by positioning the foam sheet above the air cell layer.

2. INDEPENDENCE

The innovative hand control operation enables user independence with comfort and functional control in cases where clinically advised.

3. SAFETY

Auto-weight sensing adjusts the pressure to deliver optimal pressure care within the safe and weight determined pressure range.

4. PROTECTION

The Manual Fowler Boost* mode adjusts the mattress pressure to provide increased support under the sacral area when the backrest is raised.

5. COMPACT DESIGN

The in-built and lightweight pump easily moves with the mattress and there is no additional control unit on the end of the bed to reduce the occurrence of damage and reduce tripping hazards from cords.

6. DURABILITY

The ProCair Prime features a premium Carrflex Extreme top cover which provides enhanced chemical resistance and long term performance whilst retaining superior flexibility and breathability.

7. QUIET OPERATION

The ProCair Prime is one of the quietest systems on the market at just 28dB, ensuring minimal sleep disruption to allow maximum rest and recovery.



ProCair Prime Mattress Replacement

- Designed for high end, home and aged care needs
- Easy conversion to a foam hybrid
- A unique discreetly integrated pump
- Easy to set up with automatic weight sensing



DYNAMIC MODE

HYBRID MODE



ProCair Prime can be used as a fully alternating pressure mattress (dynamic mode) or easily converted to hybrid mode.

Standard Specifications

	Single	King Single
CODE	APMPC-R03	APMPC-R03K
CAPACITY (SAFE WORKING LOAD)	30 - 200 kg	30 - 200 kg
PATIENT RISK CATEGORY	High	High
DIMENSIONS (L X W X H) MM	2000 x 900 x 180 mm	2000 x 1050 x 1800 mm
SYSTEM ALTERNATION	1 in 2	1 in 2
MATTRESS WEIGHT	12 kg	13 kg
CPR TYPE	QuickTwist CPR	QuickTwist CPR
NUMBER OF CELLS	21	21
STATIC HEAD CELLS / ZONE	3	3
NARROW FOOT CELLS / ZONE	4	4
CELL FOAM INSERT MATERIAL	High resilience PU	High resilience PU
CELL MATERIAL	TPU laminated nylon	TPU laminated nylon
TOP COVER MATERIAL	Carrflex Extreme	Carrflex Extreme
FOWLER BOOST	N/A	Manual
ARTG	289458	289458
WARRANTY	3 years	3 years
COMPLIANCE	IEC 60601-1, IEC60601-1-2, IEC60601-1-11, BS7175 Crib 5	